Manufacturers & Distributors of Quality Wire Fencing Products Unit 7, Babdown Airfield, Nr. Tetbury, Gloucestershire, GL8 8YL

Tel: 0844 561 8236 Fax: 0844 561 8237 www.uniwire.co.uk sales@uniwire.co.uk

C6/90/30

Mild Steel

C6/90/30 is a taller stock fence used in areas of low pressure and with the need for a taller option than standard fencing. It has less line wires and stay wires than the standard 8/80/15 which makes it a more cost effective option. This fence is ministry grant approved.

Mild steel stock fence does not need to be strained as tight as high tensile products. This means it is particularly useful if you have lots of turns in your fence as gradual turns can be made off intermediate posts.

Line wires	6
Distance between vertical wires	30cm
Height	90cm
Top and bottom line wires	3.00mm - 695 N/mm2
Intermediate line wires	2.5mm - 695 N/mm2
Vertical wires	2.5mm - 415 N/mm2
Roll lengths available	50m,100m
Weight of 50m roll	20.5kg

SPACING BETWEEN SUCCESIVE HORITONTAL WIRES FROM THE TOP	6 / 90 / 30 300mm 12" VERTICAL SPACING
230mm	
204mm	
180mm	
152mm	
140mm	



Manufactured to BS EN 10223. Galvanised to BS EN 10244 Class A