

Manufacturers & Distributors of Quality Wire Fencing Products Unit 7, Babdown Airfield, Nr. Tetbury, Gloucestershire, GL8 8YL

Tel: 0844 561 8236 Fax: 0844 561 8237 www.uniwire.co.uk sales@uniwire.co.uk

C8/80/22- Lamb Safe

An alternative to C8/80/15 but with 22cm (9") spacing between the vertical wires, making it ideal for sheep and lambs since the wider spacing helps prevent lambs getting their heads trapped in the fence. This fence is ministry grant approved.

Mild steel stock fence does not need to be strained as tight as high tensile products. This means it is particularly useful if you have lots of turns in your fence as gradual turns can be made off intermediate posts.

Line wires	8	
Distance between vertical wires	22cm	
Height	80cm	
Top and bottom line wires	3.00mm - 695 N/mm2	
Intermediate line wires	2.5mm - 695 N/mm2	
Vertical wires	2.5mm - 415 N/mm2	
Roll lengths available	50m, 100m, 250m	
Weight of 100m roll	27kg	

SPACING BETWEEN SUCCESIVE HORITONTAL WIRES FROM THE TOP	8 / 80 / 22 150mm VERTICAL SPACING
152mm	
140mm	
131mm	
114mm	
102mm	
83mm	
83mm	



Manufactured to BS EN 10223, Galvanised to BS EN 10244 Class A