Manufacturers & Distributors of Quality Wire Fencing Products Unit 7, Babdown Airfield, Nr. Tetbury, Gloucestershire, GL8 8YL

Tel: 0844 561 8236 Fax: 0844 561 8237 www.uniwire.co.uk sales@uniwire.co.uk

C8/80/30

An economical alternative to C8/80/15 and C8/80/22 with 30cm (12") spacing between the vertical wires. This fence is ministry grant approved.

Mild steel stock fence does not need to be strained as tight as high tensile products. This means it is particularly useful if you have lots of turns in your fence as gradual turns can be made off intermediate posts.

Line wires	8
Distance between vertical wires	30cm
Height	80cm
Top and bottom line wires	3.00mm - 695 N/mm2
Intermediate line wires	2.5mm - 695 N/mm2
Vertical wires	2.5mm - 415 N/mm2
Roll lengths available	50m, 100m, 250m
Weight of 100m roll	24.5kg

SPACING BETWEEN SUCCESIVE HORITONTAL WIRES FROM THE TOP	8 / 80 / 30 150mm 6" VERTICAL SPACING
152mm	
140mm	
131mm	
114mm	
102mm	
83mm	
83mm	



Manufactured to BS EN 10223. Galvanised to BS EN 10244 Class A